

(51) International Patent Classification ⁷ : A61M 5/00, 5/32	A1	(11) International Publication Number: WO 00/41749
		(43) International Publication Date: 20 July 2000 (20.07.00)


(74) Agent: WOO, Louis; Law Offices of Louis Woo, Suite 501,
1901 North Fort Myer Drive, Arlington, VA 22209 (US).

(43) International Publication Date: 20 July 2000 (20.07.00)

Published
With international search report.

(57) Abstract

A needle protection device (2) for a vial (16) has a collar (4) at the base of which a number of finger grippers (6) extend. The collar (4) is placed about the hub (10) of a vial (16), and pushed there along until the gripper fingers (6) snap over the bottom surface of the needle hub (10) so as to fixedly couple the collar (4) to the needle hub (10) of the vial (16). Flexibly extending from the collar (4) is a housing (6) that is pivotable to a position in alignment along the longitudinal axis of the vial (16) for enveloping the needle (12), to thereby prevent the needle (12) from being exposed to the environment. A hook (18) integrated to the inside of the housing (6) ensures that the needle (12), the housing (6) could no longer move relative to each other once the hook (18) snaps over, and traps the needle (18), as the housing (6) is pivoted to its alignment position.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Title: Needle Protection Apparatus Used With A Vial

Field of the Invention

The present invention relates to a needle protection device used with a vial that contains medicament to be injected to a patient, and more particularly for preventing further exposure of the contaminated needle once the medicament in the vial has been injected to the patient and the
5 needle has been withdrawn from the patient.

Background of the Invention

In the medical field, needle protection devices are well known. A
10 number of such devices, assigned to the assignee of the instant invention by inventor Hollister, reference the use of a needle protection device to cover a contaminated needle. These include U.S. patent 4,982,842 that discloses a universal safety adapter for use with a syringe and a needle assembly, and U.S. patent Nos. 5,139,489, 5,154,285 and 5,277,311, all
15 of which disclose, among other things, the use of a needle protection device with a VACUTAINER double ended needle. Other Hollister patents that describe needle protection devices include U.S. patent Nos. 5,232,454, 5,232,455, 5,423,765, 5,615,771 and 5,649,622.

There is currently in the market a number of vials, presealed with
20 medicament such as for example heparin, that are to be injected to a patient. The use of vials that contain medicament is more efficient in some ways than the use of a syringe insofar as the amount of medicament stored in a vial has been premeasured and, since the vial is sealed, the

problem of contamination substantially eliminated. Yet the fact remains that in order to inject a patient with the medicament of a vial, a needle has to be used. Oftentimes such needle is mounted to the vial during manufacturing of the vial. Examples of such needle mounted vials include those used with the Tubex and Carpujet applicators. Yet none of these vials configured with a needle has any prophylactic device that will prevent the exposure of the contaminated needle from the environment once the medicament in the vial has been injected to the patient and the needle withdrawn from the patient.

Summary of the Present Invention

To provide protection against accidental pricking by a contaminated needle attached to a vial, a collar that is configured to slidably fit to the needle hub of the vial is inserted over the needle hub before the needle cover is removed from the needle. The collar has extending to its lower side a number of finger extensions each of which has a hook-like gripper for mating with the bottom portion of the needle hub of the vial. Thus, when the collar is moved to the appropriate distance along the needle hub, the finger extensions would snap over the edge of the bottom portion of the needle hub so that the hooks at the end of the finger extensions will grasp onto the bottom surface of the hub. The collar, once thus secured, nonetheless is rotatable about the hub of the vial.

A housing flexibly extending from the top of the collar provides the enclosure for covering the needle extending from the vial, once the contaminated needle is withdrawn from the patient and the housing is pivoted into alignment along the longitudinal axis of the vial. A hook

mechanism inside the housing locks onto the needle once the housing is pivoted into alignment with the vial and the hook mechanism comes into contact with the needle and snaps thereover.

5 Instead of a collar, a second embodiment of the instant invention has a non-close substantially circular base that has two arms or ears extending away from the base. These two arms coact with each other when they are pressed towards each other. One of the arms has a hooked extension that interacts with the blunt extension of the other arm so that
10 when the two arms are pressed together, the hooked extension will snap over the blunt extension and the two arms are interlocked. This embodiment of the instant invention is used for those vials which needle hub substantially smoothly extends from the medicament containing body. The base of the second embodiment device is therefore configured to fit
15 over the body of the vial so that, once positioned appropriately onto the body, the arms of the base are squeezed to lock the base into position around the vial.

20 A housing that is similar to that used in the first embodiment is flexibly connected to a neck extending from the base. As before, to cover a contaminated needle, the housing is pivoted into alignment along the longitudinal axis of the vial to which the base is mounted about, so that the needle is covered by the housing. An integral hook in the housing grasps onto the needle and prevents any relative movement between the needle and the housing once the housing has been pivoted sufficiently to allow the hook to snap over the needle.

It is therefore an objective of the present invention to provide an add-on device that prevents a contaminated needle extending from a vial from being exposed to the environment.

5 It is another objective of the present invention to provide a protective device that is fixedly attached to a vial once it is fitted to the vial.

It is moreover an objective of the present invention to provide an inexpensive way of retrofitting a conventional vial such that protection is provided therefor to prevent accidental needle pricks from a needle attached thereto.

10

Brief Description of the Figures

15

The above-mentioned objectives and advantages of the present invention will become apparent and the invention itself will be best understood with reference to the following description of embodiments of the present invention taken in conjunction with the accompanying drawings, wherein:

Fig. 1a is a top view of the first embodiment of the present invention with the housing pivoted at right angle to the collar of the device;

Fig. 1b is a cross-sectional view of the housing of Fig. 1a illustrating the hook therein;

20

Fig. 1c is a cross-sectional side view of the housing of the Fig. 1a device;

Fig. 1d is a sectional side view of the first embodiment device of the instant invention;

Fig. 1e is a cross-sectional view of the collar of the Fig. 1d illustration;

5

Fig. 1f is an end view of the Fig. 1d device;

Fig. 2 is an illustration of the instant invention device having been mately coupled to a vial, and the injection applicator that is used with the vial to enable a user to eject the medicament stored in the vial;

10

Fig. 3 is a perspective illustration of a second embodiment of the device of the instant invention sans the housing;

Fig. 4a is a top view of the second embodiment device;

15

Fig. 4b is a cross-sectional side view of the second embodiment device of the instant invention; and

Fig. 5 shows the vial and the injection applicator used with the second embodiment of the instant invention as illustrated in Figs. 3 and 4.

Detailed Description of the Embodiments of the Invention

20 With reference to Figs. 1a-1d, the needle protection device 2 of the instant invention is shown to include a collar 4 and a housing 6 flexibly attached thereto by means of a living hinge 8. As best shown in Figs. 1d,

1e and 1f, collar 4 has a main section wherefrom a number of fingers 6 extend. At the tip of each of fingers 6 there is a hook tip 7. The size of collar 6 is configured to fit over a needle hub such as for example hub 10 shown in Fig. 2.

5 A second element of the needle protection device of the instant invention is housing 6 that is flexibly connected to collar 4 by means of living hinge 8. As shown, housing 6 has a longitudinal slot 12 through which a needle such as for example 12 shown in Fig. 2 can pass through when housing 6 is pivoted along the direction indicated by directional arrow 10 14 to a position in alignment with the longitudinal axis of a vial 16, so as to cover needle 12. Housing 6 is further shown to have a hook 18 integrated to the inside thereof so that, once housing 6 is pivoted into longitudinal alignment with vial 16, the bent portion 18a (Fig. 1b) of hook 18 will snap over needle 12 to therefore prevent any further relative movement between 15 needle 12 and housing 6. Once needle 12 is secured by hook 18, needle 12 is prevented from being exposed to the environment, as it remains enveloped by housing 6.

 With specific reference to Fig. 2, note that to secure device 2 to vial 16, collar 4 is inserted about hub 10 of the needle assembly of vial 16 and 20 pushed downward until hook tips 7 of collar 4 snap over the bottom surface 10a of hub 10. Since device 2 is made of a plastic material that has a given amount of flexibility and collar 4 is configured to fit closely to hub 10, when collar 4 is inserted about hub 10, its elasticity allows fingers 6 to expand until their respective hook tips snap over bottom surface 10a of 25 hub 10. At which time fingers 6 will return to their natural configured state

so that hook tips 7 are maintained behind bottom surface 10a to thereby fixedly coupled collar 4 to hub 10 of vial 16. Since collar 4 is coupled to hub 10 only due to the contact between hook tips 7 and the bottom surface 10a of hub 10, device 2 is rotatable about hub 10.

5 Vial 16 shown in Fig. 2 is a conventional type of vial that is adaptable to be mated to a Tubex type injection applicator, such as for example that designated by 20. As shown, vial 16 has a main body 16a inside of which a medicament such as for example heparin may be stored. Vial 16 is closed at its one end by hub 10 and needle 12 extending therefrom. Vial 16 is sealed at its other end by a rubber gasket 22
10 movable along the length of vial 16 that has molded thereto a screw 24. Screw 24 is threadedly mated to a threaded end 26 of injection applicator 20, which also has a turnable coupler that can be fitted to the end of vial 16 as shown by the dotted line 30. Once coupled to vial 16, coupler 28 is
15 turned so as to squeezingly secure injector 20 to vial 16. Once injector 20 is securely fixed to vial 16, the combination of vial/injection applicator functions the same way as a conventional syringe. This is due to the fact that injection applicator 20 further has a plunger 32 that, by means of threaded portion 26, is threadedly coupled to rubber gasket 22, so that by
20 pushing plunger 32 towards hub 10 along the longitudinal axis of vial 16, the medicament stored in main body 16a could be injected to a patient to which needle 12 is inserted.

 As noted above, once needle 12 is withdrawn from the patient after the medicament in vial 16 has been injected to the patient, to prevent the
25 contaminated needle 12 from being further exposed to the environment,

housing 6 is pivoted in the direction as indicated by arrow 14 to envelope needle 12. Needle 12 is secured within housing 6 by means of the interaction between hook 18 and needle 12, when hook 18 snaps over and retains needle 12 within housing 6.

5 A second embodiment of the instant invention is illustrated in Figs. 3, 4a and 4b. As shown in the perspective view of Fig. 3, the needle protection device has a non-close base 34 that has two arms or ears 36 and 38 extending therefrom. As shown, arm 36 has a blunt tip 36a whereas arm 38 has a hooked tip 38a. By pressing arms 36 and 38
10 towards each other, so that hook tip 38a snaps over blunt tip 36a, arms 38 and 36 are locked into place with respect to each other. By means of shoulders 40 and 42, arms 38 and 36 are ensured not to be forced sufficiently close towards each other so as to substantially deform the configuration of the inside circumference of base 34. Further, shoulders
15 40 and 42 prevent arms 38 and 36 from being inadvertently freed from each other by the further compressing of those arms towards each other.

 As best shown in Figs. 3 and 4b, extending from base 34 is a neck 44 at the end of which, by means of a living hinge 46, a housing 6 is attached. Insofar as housing 6 shown in Figs. 3 and 4 is the same as that
20 shown in Figs. 1 and 2, the same elements as discussed earlier are likewise present in the housing 6 for the embodiment of the instant invention as illustrated in Figs. 3 and 4. Accordingly, the same designations are used.

Fig. 5 illustrates the type of vial to which the needle protection device of the Fig. 3 embodiment may be used. As shown, vial 46 has a main body and a hub 48 extending substantially smoothly therefrom. Since hub 48 and vial 46 essentially forms a single body due to the smooth integration of hub 48 to vial 46, the collar of the first embodiment could not be used herein. Like vial 16, vial 46 also has a movable rubber gasket 22 at its open end that acts to seal the medicament content of vial 46 from the environment. A needle 50 extends from the end of hub 48.

A Carpujet type injection applicator 52 is further illustrated in Fig. 5. As shown, applicator 52 has a body 54 with one side thereof opened to the environment. An aperture 53 is formed at the opposed side of body 54. Housing 54 has a finger grip base 56. Inserted through base 56 is a cylinder 58 that extends from a base 60 that has a shape substantially mirrors that of base 56. Cylinder 58 has a groove 62 that mates with a bump protrusion (not shown) formed at the back side of base 56. Thus, a clinician can raise or lower cylinder 58 relative to base 56 by turning base 60 clockwise or counterclockwise, respectively. A plunger rod 64 is movably fitted to base 16 and cylinder 58. Rod 64 has an integral head 66 having therewithin a threaded portion 68 that mates with screw 24 of vial 46. Head 66 of the push rod is movable longitudinally within body 54, in response to the movement of rod 64.

As shown in Fig. 5, vial 46 is fitted with the needle protection device of Fig. 3. The needle protection device of Figs. 3 and 4 is attached to vial 46 as follows. First, base 34 is slipped over vial 46. Once the desired placement of base 34 with respect to somewhere along the length of vial

46 is reached, arms 36 and 38 are squeezed together until the coacting hooked and blunt ends snap together to thereby secure base 42 to vial 46. Thus secured, the sheath (not shown) that covers needle 50 could then be removed. The securing of base 34 to vial 46 of course is done before vial
5 46 is fitted within housing 54 of injection applicator 52.

To assemble vial 46 to applicator 52, base 60 is turned counterclockwise so as to lower cylinder 58 to its lowermost position within body 54. Vial 46, with neck 44 of the protection device facing the reader, is inserted into body 54 of applicator 52 so that interlocked arms 36 and 38
10 extend through aperture 53. Thereafter, rod 64 is turned so that screw 24 is threadingly fitted to head 66 of push rod 64. Base 60 is then rotated clockwise so as to raise cylinder 58 to thereby force hub 48 of vial 46 against the top inner surface of body 54. Once base 60 is turned fully clockwise, due to the interaction between groove 62 and the not shown
15 protrusion of base 56, vial 46 is tightly fitted within body 54. Thereafter, the vial device shown in Fig. 5 is usable. To discard vial 46, the reverse process is performed.

In operation, the clinician pricks the patient with needle 50, pushes the applicator rod 64 of injection applicator 52 forwards so as to cause
20 rubber gasket 22 to push, and therefore inject, the medicament stored in vial 46 to the patient. After needle 50 is withdrawn from the patient, as was done in the device embodiment of Figs. 1 and 2, housing 6 is pivoted to envelop needle 50; and hook 18 within housing 6, once snapped over needle 50, will fixedly retain needle 50 within housing 6, thereby preventing
25 needle 50 from further being exposed to the environment. Thereafter, vial

46 is unthreaded from head 66 by turning push rod 64 in a counterclockwise direction. Cylinder 58 is then lowered by turning base 60 counterclockwise. Once cylinder 58 is moved to its lowermost position, vial 46, with its contaminated needle 50 being maintained and insulated within housing 6, is removed from body 54 and discarded in the appropriate manner.

It should be appreciated that the present invention is subject to many variations, modifications and changes in detail. Thus, it is the intention of the inventor that all matter described throughout this specification and shown in the accompanying drawings be interpreted as illustrative only and not in a limiting sense. Accordingly, it is intended that this invention be limited only by the spirit and scope of the hereto appended claims.

Claims

- 1 1. Needle protection apparatus, comprising:
2 a vial having a needle hub mated to one end, a needle extending
3 away from said vial along a longitudinal axis; and
4 a needle housing having extending therefrom a collar configured to
5 slidably fitted to said hub, said collar having extending therefrom away
6 from said housing at least one gripper means for gripping said needle hub
7 so that said collar is non-removably attached to said hub once it is fitted to
8 said hub;
9 wherein said housing is hingedly connected to said collar so as to
10 be pivotable into alignment with said longitudinal axis for covering said
11 needle.
- 1 2. Apparatus of claim 1, wherein said vial has a second end to which
2 a push rod device is removably attached; and
3 wherein once said push rod device is connected to said vial, fluid
4 stored in said vial can be ejected out of said needle when said push rod of
5 said push rod device is moved towards said vial.
- 1 3. Apparatus of claim 1, wherein said gripper means is configured such
2 that once said hub is gripped by said gripper means, said collar is rotatable
3 about said hub even though it is non-removably attached to said hub.
- 1 4. Apparatus of claim 1, wherein said housing comprises a hook
2 mechanism for preventing relative movement between said needle and
3 said housing once said housing is pivoted into alignment along said

4 longitudinal axis to cover said needle and said needle is held by said hook
5 mechanism.

1 5. Apparatus of claim 1, wherein said gripper means comprises a
2 plurality of fingers extending from said collar, each of said fingers having
3 a hook-like member extending from its end, said collar being non-
4 removably held in place with respect to said hub once said hook-like
5 members of said fingers snap over the lower edge of said hub and remain
6 engaged with at least the bottom surface of said hub, said collar being
7 rotatable about said hub while said hook-like members remain in contact
8 engagement with the bottom surface of said hub.

1 6. A needle protection device, comprising:
2 a collar configured to slidably fitted to a hub of a vial from which a
3 needle extends, said collar having extending therefrom gripper means for
4 non-removably attaching said collar to said hub once said collar is mated
5 to said hub; and
6 a needle housing flexibly connected to and extending from said
7 collar, said housing pivotable into alignment with said vial to cover said
8 needle.

1 7. Needle protection device of claim 6, wherein said gripper means
2 comprises a plurality of hook-like fingers that snap and grasp onto the
3 bottom surface of said hub to thereby non-removably attaching said collar
4 to said hub, said collar being rotatable about said hub once said collar is
5 attached to said hub.

1 8. Needle protection device of claim 6, wherein said housing comprises
2 a hook means integrated inside said housing for fixedly retaining said
3 needle within said housing once said housing is pivoted into alignment with
4 said vial and said hook means snaps over said needle.

1 9. Needle protection apparatus, comprising:
2 a vial;
3 a needle mated to said vial;
4 a substantially circular base positioned about said vial said base
5 including two coacting arms, said base to be placed around said vial when
6 said two arms are not in coacting relationship with each other, said arms
7 being pressed into a locking relationship to thereby fixedly attach said base
8 to said vial once said base is appropriately placed around said vial;
9 a housing flexibly connected to said base, said housing pivotable
10 towards said needle;
11 wherein once said base is fixedly attached to said vial, said housing
12 is pivoted to be in alignment with said needle to cover said needle.

1 10. Needle protection apparatus of claim 9, wherein one of said arms
2 has at its end thereof a hook extension that snaps onto the end of the
3 other of said arms when said arms are pushed towards each other to
4 thereby lock said base into position around said vial.

1 11. Needle protection apparatus of claim 10, wherein said arms each
2 have a shoulder extending towards the other arm so that when said arms
3 are pushed towards each other, the shoulders of said arms prevent said
4 arms from being compressed beyond a given point to thereby ensure that

5 further compressing of said arms will not free the end of said other arm
6 from said hook extension of said one arm.

1 12. A needle protection device, comprising:

2 a clamp-like base having two integral arms extending away from
3 said base, one of said arms having a first end that coacts with a second
4 end of the other of said arms when said arms are moved towards each
5 other, said arms being locked with each other when said first end mates
6 with said second end as said arms are pressed together to surround the
7 a vial wherefrom a needle extends, said base being fixedly coupled to said
8 vial when said arms are locked with each other; and

9 a housing flexibly extending from said base and pivotable to a
10 position along the longitudinal axis of said vial, said housing being
11 configured to prevent said needle from being exposed to the environment
12 when it is pivoted to said position.

1 13. Needle protection device of claim 12, wherein said first end
2 comprises a hooked extension and said second end comprises a blunt
3 extension, said hooked and blunt extensions being locked when said
4 hooked extension snaps over said blunt extension.

1 14. Needle protection device of claim 12, wherein said housing
2 comprises a hook integral of said housing that locks onto said needle to
3 thereby prevent further relative movement between said needle and said
4 housing when said housing is pivoted to said position.

1/4




FIG. 1c




FIG. 1f




FIG. 1a




FIG. 1d




FIG. 1b








FIG. 1e

2/4



3/4



4/4




FIG. 5

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US00/00454

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) :A61M 5/00, 32

US CL :604/192, 263

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 604/110, 187, 192, 198, 220, 263

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EAST

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X ---	US 5,490,841 A (LANDIS) 13 February 1996, entire document.	1-4, 6, 8
Y		5, 7, 9-14
Y ---		5, 7
A		9-14
	US 5,843,047 A (PYROZYK et al.) 1 December 1998, entire document.	

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
B earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*G* document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means	
P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

10 MARCH 2000

Date of mailing of the international search report

17 APR 2000

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

ERIC KLINE

Telephone No. (703) 305-7350